

Visqueen Megafilm LPCB approved to LPS1207



- **LPCB Approved to LPS1207**
- **Unique mould pattern creates anti-slip surface**
- **Cover large areas fast - saves labour time and costs**
- **Manufactured in the UK by Visqueen**

Visqueen Megafilm is manufactured in the UK and a range of flame retardant temporary floor protection films used to protect a diverse range of surfaces. All of the Visqueen Megafilm® range is moulded (embossed) flame retardant film designed to suit both carpet & hard floor applications, including wooden, vinyl & stone flooring. Visqueen Megafilm® offers complete protection during refurbishment and redecoration and is available in a range of grades.

Product Range

Our comprehensive product range includes the following:

- | | |
|---|-------------------|
| • Visqueen Megafilm Light Duty LPS1207 | 1.5m x 167m Green |
| • Visqueen Megafilm Medium Duty LPS1207 | 1.5m x 100m White |
| • Visqueen Megafilm Heavy Duty LPS1207 | 1.5m x 100m Blue |
| • Visqueen Megafilm Heavy Duty LPS1207 | 1m x 100m Blue |

All the above products are heavy embossed for greater protection except for the Light Duty. The medium and heavy duty grades are suitable for areas with heavy footfall provided the application and installation guidelines are followed. The Light Duty can be suitable for carpet and dust protection applications and is a cost effective substitute to self adhesive and woven polypropylene protective films.

For full information on the above products please see our technical table on page 3 or use our [product selector](#) on our website.

System component

- Megafilm Flame Retardent Tape 75mm x 33m

Ensure flame retardant continuity by using Visqueen FR Tape at lap joints and perimeters.

Why use flame retardant protection?

A flame retardant protective material should be used where there is a potential risk of fire during any new build or refurbishment project. Also, when insurers have a clause in their policy requesting compliance with 'The Joint Code of Practice' or with LPS 1207, a temporary flame retardant protective material should be used.

The use of non-certified LPS 1207 materials could result in the withdrawal of insurance cover in the event of fire

Installation

Visqueen Megafilm® is available in a manageable roll size allowing you to cover large areas fast. The ease of installation helps speed up the protection process, reducing the risk of damage to exposed finishes. Visqueen Megafilm® is flexible and durable, ensuring an all round easy to install protection system.

Preparation

To ensure the highest performance of the material, protection should be installed as soon as all surfaces to be covered are clean and are fully cured where necessary.



Laying

Material should be laid print side up, unless directed otherwise. All rolls are supplied with fitting instructions.

Cut and Fit

Unroll the material and cut to fit desired coverage area . For larger area applications where jointing is required allow an overlap of at least 50mm; any pyramids will interlock to provide a trip free joint when taped securely. Pull protection taut to ensure that the material lies flat. Smooth down all taped joints and perimeters by applying pressure along their length.

Tapes

For total protection, tape perimeter edge of megafilm and overlay adjacent sheets by 50mm and seal with Visqueen Megafilm® FR tape.

Further Information

Storage & Handling: The materials used in Visqueen Megafilm® are chemically stable and inert and are free of both solvents and aggressive chemicals. They are also clean and safe to use and contain no volatiles to 'seep' out. Due to their robust nature, Visqueen Megafilm® requires no special conditions for storage, transport, handling or usage.

Custom Print Facility: Your company message or logo can be printed onto the film helping to raise your company profile and encapsulate your audience.


Flame Retardant: Visqueen Megafilm is manufactured with the addition of special additives to the polyethylene. Once heated (i.e. as in burning) the polyethylene and special additives (i.e. finished product) react together to produce a gaseous form* that limits the access of atmospheric oxygen to the flame and the burning process is stopped through the lack of oxygen (i.e. Fire Blanket effect). Vapours can be given off at temperatures above 115°C*.

LPS (Loss Prevention Standard) 1207

Visqueen Megafilm® is certified by the Loss Prevention Certification Board in compliance with Loss Prevention Standard LPS 1207 which requires that the following standards are met:

- Ignitability-Small and Large Tests (BS 476: Part 12:1991 and LPS: BS5852)
- Smoke Emissions Test (prEN 2824 and prEN 2825)
- Toxic Gas Emission Test (prEN 2824 and prEN 2826)
- Critical Oxygen Index (BS 2782: Part 1: Method 141: 1986)

Availability: Visqueen Megafilm® is available from selected Temporary Site Protection Specialist Merchants throughout the UK .



Visqueen Megafilm LPCB approved to LPS1207

Appendix A

About Visqueen

Visqueen is the market leader in the manufacture and supply of structural waterproofing and gas protection systems. Visqueen offers the complete package – a proven, reliable range backed by a technical support service that goes unmatched in the market - everything you would expect from a reputable and ethical company.

Complete Range, Complete Solution

- Structural Waterproofing
- Damp Proof Course
- Damp Proof Membranes
- Gas Protection and Gas Venting
- Vapour Control Layers
- Stormwater Protection

Download Library

- Technical Datasheet
- Standard Details
- Technical Service
- Visqueen Gas Protection Brochure
- NBS Clauses
- BBA Certificates
- Material Safety Datasheets
- Specification Guide

Find your local stockist

Search our directory of Visqueen specification [Specialist Centres](#) to locate your nearest Visqueen Partner.

Technical support throughout your project

We are specialists in our field and can help you specify the correct solutions with the necessary performance levels, in accordance with building regulations.

- Nationwide site support team
- Specification advice
- Installation guidance & project sign off
- System design including CAD details

CPD Seminars and Training Academy



Gas Protection CPD

The specification, technical design, and installation of gas protection systems, enabling the sustainable regeneration of brownfield sites.



Structural Waterproofing CPD

The specification, technical design, and installation of structural waterproofing systems for protection against water and damp ingress in both above and below ground projects.



Visqueen Training Academy

We are now able to offer exclusive in depth training opportunities on a wide variety of Visqueen products at our Training Academy.



Visqueen Special Projects

We provide high-level expertise, comprehensive support and experience in all types of waterproofing and gas protection.

VISQUEEN

Part of RPC lpi group

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG

0333 202 6800 enquiries@visqueen.com www.visqueen.com

The information given in this datasheet is based on data and knowledge correct at the time of printing. Statements made are of a general nature and are not intended to apply to any use or application outside any referred to in the datasheet. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.

