

## VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

### Features and benefits

- Utilises Visqueen's Advanced Adhesion Technology - twice the adhesion in cold weather
- Complete system - use with Visqueen HP Tanking Primer to obtain best performance
- Flexible - can be cut and shaped to various applications
- Multi-use - ideal for complex junctions, stanchions, patchwork and terminations
- Aluminium core - gas resistant in accordance with BS8485:2015+A1:2019

### Product description

VisqueenPro Detailing Strip is a composite of PET/aluminium and a high performance cold weather butyl compound. It is available in roll format, 300mm x 10m and 500mm x 10m.

### Approvals and standards

- Third party accreditation - BBA certification
- Conforms to the specification requirements of BS 8485:2015 + A1:2019
- Suitable for all Characteristic Gas Situation (CS) ground gas regimes
- Conforms to the specification requirements of NHBC Amber 1 and Amber 2 applications
- Conforms to the specification requirements of BR 211:2015
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015

### Usage


Visqueen ProDetailing Strip can be used for gas protection systems, waterproofing system, and damp proofing systems for use on concrete, blockwork, brickwork, particle boards, steel work, steel stanchions and wooden structures for both vertical and horizontal application.

VisqueenPro Detailing Strip is post applied against the structure, steel stanchions and forms complex detailing. It forms a 2-part system with the Visqueen HP Tanking Primer. The Visqueen HP Tanking Primer is a single component primer, for use see separate datasheet.

### System components

- Visqueen HP Tanking Primer, 5L

### Find your local stockist



## VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

### Storage and handling

Store in warm (above 5°C), dry and clean environment in its current packaging. The product must be stored upright.

### Preparation

Surfaces must be smooth and free from sharp protrusions, ensure the surface and working area is not water logged and is frost free. When applying to blockwork or brickwork the joints must be flush pointed, in demanding applications the masonry face must be rendered prior to applying the Visqueen Pro Detailing Strip. Prior to applications the surface should be sealed using Visqueen HP Tanking Primer and allowed to dry thoroughly. The Visqueen HP Tanking Primer must not be used on Insulation or ICF systems, please contact Visqueen Technical Department.

### Installation

All lap joints should be a minimum of 150mm and must be pressed and rolled to form a continuous bond to ensure gas and water tightness.

For complex detailing the detailing strip can easily be cut, shaped and formed around the area.

For patch work - when membranes are punctured, VisqueenPro Detailing Strip can be lapped at least 150mm beyond the extents of the puncture.

### Usable temperature range

It is recommended that Visqueen membranes and system components should be used above 5°C

### Additional information

When applying to blockwork or brickwork the joints must be flush pointed, in demanding applications the masonry face must be rendered prior to applying the Visqueen Pro detailing Strip. The Visqueen HP Tanking Primer must not be used on Insulation or ICF systems, please contact Visqueen Technical Department.

**VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m**

Property	Value
Width	300mm and 500mm
Length	10m
Application temperature range	-5°C to 40°C
Peel Adhesion EN12316, Steel ASTM D1000, in N/cm @ 5°C	
Polyethylene	20.7
Polyethylene with no static charge	21.2
Steel	26.9
Concrete	28.8
Mean water vapour resistance factor , EN1931, u	3960000
Mean water vapour diffusion equivalent air layer thickness EN1931, (Sd) in m	4752
Mean water vapour resistance, EN1931, MNs/g	23760
Mean water vapour permeability, EN1931, g/m2/day	0.03

**Health and safety information**

Please refer to material safety datasheet

## VisqueenPro Detailing Strip, 300mm x 10m, 500mm x 10m

### About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website ([www.visqueen.com](http://www.visqueen.com)) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or [enquiries@visqueen.com](mailto:enquiries@visqueen.com)

### Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

### Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

### Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

### Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

### Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.