

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Features and benefits

- Part of the Visqueen air and vapour control layer (AVCL) range

Product description

VisqueenPro Vapour Edge Tape is a single sided aluminium flashing tape coated with an acrylic adhesive and a removable release film protecting the adhesive coating.

The product is available in roll format 150mm x 15m.

Approvals and standards

- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

Usage

VisqueenPro Vapour Edge Tape is used for gap bridging or as a flashing to seal the Visqueen air and vapour control layer at the perimeter of the installation onto substrates such as concrete, timber, plastic and steel.

System components

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Storage and handling

Store in warm, dry and clean environment in its original packaging. The flashing tape should not be exposed to long periods of ultraviolet light.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

The lap area of the Visqueen air and vapour control layer and the adjacent abutting substrate should be clean, dry and free from contamination such as dust.

The flashing tape can be cut with a sharp retractable safety knife.

Installation

When using VisqueenPro Vapour Edge Tape apply equidistant over the junction to be sealed. Apply pressure to the jointed area to ensure adhesion. Once the flashing tape is applied, the completed lap should be well rolled with firm pressure to ensure a completely sealed junction has been formed and continuity with the adjacent substrate has been achieved.

To aid formation, where possible jointed areas should be made over a solid substrate.

Usable temperature range

It is recommended that VisqueenPro Vapour Edge Tape should be installed above 5°C.

Additional information

Care should be taken to prevent the AVCL from becoming punctured, stretched or displaced when installing plasterboard or other construction board over the installed AVCL.

For additional detailing information, contact Visqueen Technical Services +44 (0) 333 202 6800.

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

Property	Value
Roll dimensions	150mm x 15m
Application temperature range	5°C to 40°C

Health and safety information

Refer to the VisqueenPro Vapour Edge Tape safety datasheet (SDS).

VisqueenPro Single Sided Vapour Edge Tape, 150mm x 15m

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive two day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.