

Declaration of Performance

Unique identification code of the product-type:

1.	Product name	Colour	Thicknesses
	Ecomembrane	Black	250, 300 and 500 micron
	Ecomembrane	Blue	250, 300 and 500 micron

2.	Intended use	Plastic sheet for damp proofing
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)	Visqueen Maerdy Industrial Estate Rhymney, UK, NP22 5PY
4.	Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):	Not relevant
5.	System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 2+
6.	a. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13967:2017
	Notified body/ies	British Board of Agrément 0836 SGS Italia 1381
6	b. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued	Not relevant

7. Declaration performance

Essential Characteristics		Performance	Harmonised Technical Specification
Reaction to Fire		F	EN 13967:2017
Water tightness		Pass	
Resistance to Impact		200mm	
Resistance to static loading		20Kg	
Durability against heat ageing		Pass	
Durability against chemicals		Pass	

To view all test results please see our Ecomembrane Technical Datasheet (TDS)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Place

Signature

Date

DoP N°: VBP/CPR/DPM002

Edition: December 2020

Issue 02

VISQUEEN

Derbyshire, UK



Cameron Yates
Technical Product Manager

17/11/2020